


DATACARD® SR200 RETRANSFER CARD PRINTER



The Datacard® SR200 retransfer card printer offers high-quality single-side retransfer printing in a compact, affordable design.

Cost-effective over-the-edge printing

Ideal for printing high-quality cards, the Datacard® SR200 retransfer card printer delivers full-color, over-the-edge, single-sided printing on a variety of materials. Electronic locks protect input cards and supplies. This highly affordable printer is also durable enough to offer a lifetime warranty on the printhead.

Essential capabilities for high-quality results

- **Improved image quality.** Retransfer printing delivers vivid results with over-the-edge coverage for a wide range of applications.
- **Excellent material compatibility.** Print high-quality images on a range of card materials, including PVC, ABS, PET, PET-G and polycarbonate.
- **Maximum security.** Electronic locks help control access to cards and ribbons, and the security erase feature blocks out black text on used YMCK ribbons to protect sensitive cardholder data.
- **Exceptional ease of use.** The SR200 printer offers easy loading of cards and color-coded ribbon cartridges. The display panel also provides timely status information to the user.
- **Maximize security and durability.** Protect cards from threats and help extend card life with the optional Datacard® LM200 card laminator, which applies Datacard® topcoats and DuraGard® laminates.

DATACARD® SR200 RETRANSFER CARD PRINTER



Easy-to-read LCD panel

Easy-loading 100-card input hopper allows cards to be added during printing

Color-coded retransfer film cassette simplifies loading

High-capacity, easy-to-load ribbon cassette reduces downtime

Optional Datacard® LM200 single-sided card laminator applies topcoats and security laminates

The Datacard® SR200 retransfer card printer can produce high-quality, single-sided cards on a variety of materials.

Standard Features

- Print capabilities
 - One-sided printing
 - Over-the-edge full-card printing
 - Full-color images
- Printing method
 - Dye sublimation retransfer
- Connectivity
 - USB 2.0 connectivity
 - Ethernet 10/100 Base-T bi-directional networking supported on Microsoft® Windows® 2000, XP and Windows Vista® operating system
- Capacity
 - Input hopper: 100 cards, 0.030 in. (0.76 mm)
 - Output hopper: 100 cards, 0.030 in. (0.76 mm)
- Print driver
 - Windows 2000, XP and Windows Vista operating systems
 - Installation of up to seven printers per PC
- Security features
 - IPSEC encrypted networking security
 - security erase of black panel text on YMCK ribbons
 - Electronic locks for cards and supplies
- User-friendly operation
 - Automatic card feed
 - Easy access components include quick change ribbon and laminate cassettes
 - Reject card slot
- Warranties
 - 24-month standard depot warranty
 - Lifetime printhead warranty

Options

- Bend remedy
- Laminator

Specifications

- Physical dimensions (SR200)
 - L 13.2 in. x W 12.7 in. x H 13.5 in. (335 mm x 343 mm x 322 mm)
- Physical dimensions (LM200)
 - L 13.2 in x W 8.3 x H 14.2 in. (210 mm x 330 mm x 360 mm)
- Weight (SR200)
 - 29.5 lbs. (13.4 kg)
- Weight (LM200)
 - Less than 24.3 lbs. (11.0 kg)
- Print resolution
 - 300 dots per inch (dpi)
- Print speed
 - Prints four-color, one-sided card in 30 seconds
- Laminate Speed (LM200)
 - Approximately 21 seconds
- Card types accepted (ISO ID-1/CR-80 size)
 - 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm)
 - PVC, ABS, PET, PET-G, Polycarbonate
- Card thickness accepted
 - 0.25 mm to 1.0 mm (10 mil to 40 mil)
- Operating environment
 - 60° - 86° F (15° - 30° C)
 - 35 - 70% relative humidity
- Electrical requirements (dual-voltage, auto-sensing)
 - 100/120V, 50/60 Hz
 - 220/240V, 50/60 Hz

Agency approvals and clarifications

- UL
- CE
- CCC
- FCC
- RoHS Compliant

Supplies

- Datacard® Certified Supplies featuring Intelligent Supplies Technology™
 - Automatic ribbon identification and validation
 - Automatic printer settings and offsets
 - Low ribbon warning
- Ribbons
 - YMCK ribbon (1,000 images)
 - YMCK-PO peel-off ribbon (750 cards)
- Retransfer film
 - InTM retransfer film (1,000 images)
- Topcoats and laminates
 - DuraGard® 1.0 mil Clear Laminate (600 images)
 - DuraGard® 1.0 mil Secure Laminate (600 images)
 - DuraGard® 0.6 mil Clear Laminate (600 images)
 - Clear topcoat (1,000 images) Secure topcoat (1,000 images) DuraGard® 0.6 mil Secure Laminate (600 images)

DatacardGroup

PHRS Card Solutions
Phone: +27 86 633 978
Phone: +27 12 329 6216
Fax: +27 329 6188
Fax t mail: +86 2420 918
Email: lynette@phrs.co.za
web: www.phrs.co.za

Datacard, DuraGard and Intelligent Supplies Technology are registered trademarks, trademarks, service marks and/or copyrights of DataCard Corporation in the United States and/or other countries. Microsoft, Windows and Windows Vista are registered trademarks of Microsoft Corporation. Names and logos on sample cards are fictitious. Any similarity to actual names, trademarks or tradenames is coincidental.

©2010-2011 DataCard Corporation. All rights reserved. Specifications subject to change without notice.